



SDE METAL ANTI CORROSIVE FLEXIBLE PRIMER

PRODUCT DESCRIPTION

SDE METAL ANTI CORROSIVE CROSS POLYMER FLEXIBLE PRIMER is a high-solids rust-inhibitive alkyd primer with anti-corrosive properties. It is easy to apply by spray, is fast drying, and can be top-coated with alkyd and latex coatings.

PROPERTIES:

SDE METAL ANTI CORROSIVE FLEXIBLE PRIMER is a high-solids rust-inhibitive compound.

AREA OF USE:

SDE METAL ANTI CORROSIVE FLEXIBLE PRIMER is ideal for architectural and light commercial construction, and is ideal for application on steel to protect against atmospheric exposure. With excellent impact resistance, it is also suitable for use on vehicles.

ADVANTAGES:

- Easy to Use.
- · Fast Drying.
- Easy to smooth down (sand)
- Impact Resistant.

METHOD OF USE:

- Make sure the surface is clean, clear, sound and free of grease and foreign matter.
- Apply one coat of SDE METAL ANTI CORROSIVE FLEXIBLE PRIMER by brush, roller or spray.
- Sand lightly and apply another coat of SDE METAL ANTI CORROSIVE FLEXIBLE PRIMER if needed.
- Apply the top coat of Polyurethane Or Super cross blend Urethane coatings
- Clean the tools using white spirit.

TECHNICAL INFORMATION:

| PRODUCT TYPE | Anti-Corrosion Primer |
|-------------------------|---|
| BINDER | Alkyd Resin |
| COLOURS | White – Grey – Red - Black. |
| INITIAL DRYING TIME | 30 Mins |
| RECOAT IN | 3 – 4 Hours |
| FINAL DRYING TIME | 24 Hours |
| VISCOSITY @ 25 c | 115 – 120 ku |
| SOLID CONTENT BY VOLUME | 53% (± 2%) |
| SOLID CONTENT BY WEIGHT | 77% (± 2%) |
| SPECIFIC GRAVITY | 1.47 (± 0.02) |
| DILUTION | White Spirit |
| AVERAGE CONSUMPTION | 12 – 16 m ² / Lit / Coat (depending on surface |
| RATE | Condition) |
| SHELF LIFE AND STORAGE | 1 Year from the production date provided. Store in |
| | sealed original packages away from direct sunlight. |

HEALTH & SAFETY:

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material in the safety data sheet.

NOTES:

The information given in this leaflet is based upon laboratory research, as well as extensive field work and application experience. All products are subject to standard conditions of sale which are available upon request. This information is based on **Safety Direct Egypt's** present state of knowledge and is intended to provide general information on **Safety Direct Egypt's** products and their methods of use.

Date of Issue: November 2018

The information given in this data sheet represents test results & practical experience obtained under controlled conditions, and are correct to the best of our knowledge. However, as products are often used under different conditions, we can only guarantee the quality of our product, and reserve the right to change data without further notice.

