



SDE POLYURETHANE

PRODUCT DESCRIPTION

SDE POLYURETHANE is a highly durable flexible one-component polyurethane wood lacquer. It is designed for use on wooden surfaces subject to heavy wear such as floors, stairs and worktops.

PROPERTIES:

SDE POLYURETHANE is a single component varnish manufactured from polyurethane resins.

AREA OF USE:

SDE POLYURETHANE is ideal for use on wood flooring, worktops, staircases, marine floors and other wooden areas subject to heavy wear.

ADVANTAGES:

- Extremely tough finish.
- 2 coat application in 1 day.
- Area back in service after 24 hours
- · Low odour.
- Resistant to household chemicals and hot water.
- Easy to Use.

METHOD OF USE:

- Make sure the surface is clean, clear, sound and free of grease and dust.
- Apply two or three coats by brush, roller or spray.
- Apply two coats of SDE POLYURETHANE from Safety Direct Egypt.
- Clean the tools using white spirit.

TECHNICAL INFORMATION:

PRODUCT TYPE	Wood Varnish
BINDER	Polyurethane
COLOURS	Transparent- can be tinted using Safety Direct Wood
	colour Chart.
INITIAL DRYING TIME	1 - 2 hours
VISCOSITY @ 25 c	93 (± 2) ku
SOLID CONTENT BY VOLUME	48 (± 2%)
SOLID CONTENT BY WEIGHT	57 (± 2%)
SPECIFIC GRAVITY	0.94 (± 0.02)
DILUTION	White Spirit
AVERAGE CONSUMPTION	12 – 16 m ² / Lit / Coat (depending on surface
RATE	Condition)
SHELF LIFE AND STORAGE	3 Years from the production date provided. Store in
	sealed original packages away from direct sunlight.

HEALTH & SAFETY:

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material in the safety data sheet.

NOTES:

The information given in this leaflet is based upon laboratory research, as well as extensive field work and application experience. All products are subject to standard conditions of sale which are available upon request. This information is based on **Safety Direct Egypt's** present state of knowledge and is intended to provide general information on **Safety Direct Egypt's** products and their methods of use.

Date of Issue: November 2018

The information given in this data sheet represents test results & practical experience obtained under controlled conditions, and are correct to the best of our knowledge. However, as products are often used under different conditions, we can only guarantee the quality of our product, and reserve the right to change data without further notice.

