



SDE SATIN

PRODUCT DESCRIPTION

SDE SATIN is an economic matt emulsion undercoat paint for interior use. It is suitable for most surfaces. **SDE SATIN** is available in white and can be manually tinted by **SAFETY DIRECT EGYPT** colourants.

PROPERTIES:

SDE SATIN is based on acrylic copolymers, fillers and additives to ensure efficiency, opacity, and easy application.

AREA OF USE:

SDE SATIN is suitable for most old and new building surfaces such as plastered walls, gypsum board, fair-faced concrete and plywood. It is ideal as an undercoat for use in apartments, office buildings, governmental establishments and housing projects.

ADVANTAGES:

- Economic undercoat.
- Does not turn yellow or change colour.
- Medium consumption rate.
- Average coverage strength.
- Environmentally friendly.

METHOD OF USE:

Surface Preparation:

- Make sure the surface is clean, clear, sound and free of grease and foreign matter.
- Prime the surface using SDE SUPER SEAL primer from Safety Direct Egypt.
- Level and smooth down the surface using **SDE ACRYLIC PUTTY** from **Safety Direct Egypt**.

Finishing:

- Apply two coats of **SDE SATIN** by roller, brush or spray gun.
- Clean tools using normal tap water.

WHERE SAFETY COMES FIRST! www.antislipegypt.com

TECHNICAL INFORMATION:

PRODUCT TYPE	Matt Emulsion Paint
BINDER	Colypolymer
COLOURS	White – can be tinted
INITIAL DRYING TIME	20 – 30 minutes
RECOAT IN	4 – 6 hours
FINAL DRYING TIME	24 Hours
VISCOSITY @ 25 c	120 -125 ku
SOLID CONTENT BY VOLUME	40 % (± 2%)
SOLID CONTENT BY WEIGHT	63 % (± 2%)
SPECIFIC GRAVITY	1.6 (± 2%)
DILUTION	With Water
AVERAGE CONSUMPTION	7 – 8 m² / Lit / Coat (depending on surface Condition)
RATE	, , , , , , , , , , , , , , , , , , , ,
SHELF LIFE AND STORAGE	2 Years from the production date provided. Store in
	sealed original packages away from direct sunlight.

HEALTH & SAFETY:

Avoid prolonged contact with eyes and skin. For detailed information refer to relevant material in the safety data sheet.

NOTES:

The information given in this leaflet is based upon laboratory research, as well as extensive field work and application experience. All products are subject to standard conditions of sale which are available upon request. This information is based on **Safety Direct Egypt's** present state of knowledge and is intended to provide general information on **Safety Direct Egypt's** products and their methods of use.

Date of Issue: November 2018

The information given in this data sheet represents test results & practical experience obtained under controlled conditions, and are correct to the best of our knowledge. However, as products are often used under different conditions, we can only guarantee the quality of our product, and reserve the right to change data without further notice.

