



## SDE WATERBASED COPOLYMER SEALER DATA SHEET

#### PRODUCT DESCRIPTION:

This Surface Sealer is a highly-effective, water-based, Acrylic polymer, impregnating sealer formulated to help protect virtually any surface from water, mild chemicals and oil born stains. Surface Sealer provides an invisible barrier resistant to stains, while allowing the surface to properly breathe. All natural stone should be sealed with an impregnating sealer to protect the surface of the stone from mild chemicals, oil and water stains. Sealing your grout, it stops dirt and grease from soaking in and staining the grout.

## **SURFACES:**

Quarry Tile. Ceramic Tile. Porcelain Tile. Glazed Tile. Marble. Granite. Travertine. Slate. Grout. Quartz. Brick. Terrazzo. Acrylic. Wood.

#### **FEATURES:**

PROTECTS & creates an invisible barrier to stains, while allowing the surface to breathe. Reducing bacteria growth in the porous surfaces.

### **CURES FAST:**

Areas may be opened for foot traffic in 2 hours. Achieves full cure in 24 hours.

## **PRODUCT SPECIFICATIONS:**

pH (concentrate 7.35-8.25.

Appearance White opaque, thin liquid.

Fragrance Characteristic.

Freezing Point About 32°F

Solubility in Water Complete

Flash Point None to Boiling

**INGREDIENTS** 

Water 7732-18-5

Acrylate Copolymer TRADE SECRET

WHERE SAFETY COMES FIRST! www.antislipegypt.com

### **PRODUCT AVAILABILITY:**

1 litre & 5 litre containers

# **DIRECTIONS FOR USE:**

Surface must be clean, dry and free of coatings or sealers.

Clean the floor first.

Always test a small area to check for desired outcome. Coverage is approx.

10-12 Square meters, Depending on porosity of the surface.

- 1. Apply evenly using a brush, roller, cloth, sponge or sprayer.
- **2.** Any excess sealer that does not penetrate within 3 to 5 minutes, buff dry with an absorbent towel or carpet bonnet.
- 3. Highly porous surfaces may require a second or third application to give full protection.
- 4. Wait a minimum of 1 hour between applications.
- **5.** Allow a cure time of 2 hours before opening for foot traffic. A full cure is achieved in 24 hours.

## TIP:

Surface temperature must be between 50° - 100° F (10° - 32° C). Will protect against mild splash of acid or caustic chemicals. Protect non-recommended surfaces from contact as product may damage these surfaces. May darken some materials.

WHERE SAFETY COMES FIRST! www.antislipegypt.com

## FOR INDUSTRIAL USE ONLY

### **IMPORTANT:**

Use only as directed.

Do not mix with anything unless recommended since harmful conditions and poor performance could result.

Do not pour unused product back into original container.

All floors are slippery when wet. To prevent falls, exercise care when working and block off traffic with "Caution" signs until floor is completely dry.

#### WARNING

May cause damage to liver or respiratory tract through prolonged or repeated exposure.

Prevention do not breathe dust / fume / gas / mist / vapours / spray.

Get medical advice / attention if you feel unwell.

Storage - Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

Disposal Dispose of contents / containers in accordance with local / regional / national / international regulations.

#### **KEEP OUT OF REACH OF CHILDREN**

#### PERSONAL PROTECTION:

Respiratory Protection: Not needed in normal use. Ventilation: Use with adequate ventilation. Eye Protection: Safety glasses are recommended. Protective Gloves: Protective gloves are recommended. Other Protective Clothing or Equipment: Wear clothing as necessary to prevent skin contact.

#### TRANSPORTATION INFORMATION: U.S. DOT

Proper Shipping Name: Not Regulated by DOT.

Marine Pollutant: No

The information given in this data sheet represents test results & practical experience obtained under controlled conditions, and are correct to the best of our knowledge. However, as products are often used under different conditions, we can only guarantee the quality of our product, and reserve the right to change data without further notice.

